

**Our Products Make Your Product Better®**

To learn more about EMAC's products and services and how they can help your project

[http://ftp.emacinc.com/Tech\\_Info/About\\_EMAC\\_Products\\_and\\_Services.pdf](http://ftp.emacinc.com/Tech_Info/About_EMAC_Products_and_Services.pdf)



Authorized Distributor, Integrator, and Value-Added Reseller



Manual downloaded from <ftp.emacinc.com>

For purchase information please contact [info@emacinc.com](mailto:info@emacinc.com)

For technical support please submit a ticket at [www.emacinc.com/support](http://www.emacinc.com/support)

# ICOP-6025V

4MB/4S/VGA/LCD/GPIO/DOC




Unit: mm

## Specifications

<b>SoC</b>	DM&P(ALi) M6117D System-on-Chip CPU 386SX-40MHz Real Time Clock with Lithium Battery Backup
<b>Bus</b>	PC/104 standard compliant
<b>BIOS</b>	AMI BIOS
<b>System Memory</b>	Onboard 4MB EDO RAM, up to 20MB (optional)
<b>Watchdog Timer</b>	Software programmable from 30.5 us to 512 seconds
<b>VGA</b>	TOPRO TP6508IQ Chipset VGA and Mono/STN/DSTN/TFT Flat Panel interface support Onboard 1MB VGA Memory, support resolution up to 1024x768, 256 colors
<b>Flash Disk Support</b>	MSTI EmbedDisk Module (16MB and above) PQI DiskOnModule (16MB and above) M-System DiskOnChip 2000 (16MB and above) Winbond DIP Package Flash W29C040 (512KB)
<b>I/O Interface</b>	Enhanced IDE port x1 FDD port x1 RS-232 port x3 RS-232/485 port x1 Parallel port x1 16-bit GPIO port x1
<b>Connectors</b>	72-pin socket for SIMM Module x1 2.54mm 44-pin box header for IDE x1 2.0mm 44-pin box header for LCD x1 2.54mm 34-pin box header for FDD x1 32-pin DIP socket for DOC x1 2.54mm 26-pin box header for Printer x1 2.54mm 20-pin box header for 16-bit GPIO x1 2.54mm 10-pin box header for RS-232 x3 6-pin P8 Power connector for Power Input 2.54mm 5-pin box header for Keyboard x1 2.54mm 2-pin header for RS-485 x1 2.54mm 2-pin header for Reset x1 External 15-pin D-Sub female connector for VGA External 9-pin D-Sub male connector for RS-232 x1 External Mini DIN connector for Keyboard/Mouse x1
<b>Power Requirement</b>	Single Voltage +5V @770mA

<b>Weight</b>	200g
<b>Board Size</b>	184 X 122mm (7.24 x 4.8 inches)
<b>Operating Temperature</b>	-20°C ~ +70°C



	COM1	COM2	COM3	COM4
<b>Shared (default)</b>	JP8 1-2 Close JP9 1-2 Close	IRQ 3	IRQ 4 IRQ 4	IRQ 3
<b>Independent</b>	JP8 2-3 Close JP9 2-3 Close	IRQ 3	IRQ 4 IRQ 4	IRQ 11 IRQ 10

ICOP-6025V supports 4 serial ports. User can easily choose Shared/Independent IRQ by setting JP8 and JP9.



## Packing List

- ICOP-6025V x1
- CD for User's Manual & Driver x1
- Cable
  - AT BUS x1
  - PRINT+F x1
  - RS-232 x3 (ICOP-6025V)
  - RS-232 x1 (ICOP-6024V)
  - YKB x1

## Ordering information:

- ICOP-6025V** M6117D Half-Size CPU Module
- DM&P 4/16MB SIMM Module**
- LCD-064-SET** 6.4" LCD Kit

- 1 Mity/Tiny Module
- 2 PC/104 Module
- 3 3.5"/ATX Module
- 4 Half-Size Module
- 5 Peripheral Module
- 6 Accessories