




### Description:

The PPC-070C capacitive touchscreen computer is unique and successful for a reason. The PPC-070C is fanless and silent operation from lack of moving parts and all aluminum design. We have been able to offer reliable and industrial grade touchscreen solution that functions as a standard pc system.

### Features

- Edge-to-edge glass IP65 rated
- 10-finger multitouch touch screen Panel
- Intel Celeron N2807 CPU Intel HD Graphics
- 2GB RAM (expandable to 4GB)
- 64GByte SSD included
- 32Bit and 64Bit support Linux and Win 7/Win 8/Win10 support
- Pre-installed Linux Ubuntu OS
- Consumer and industrial interfaces
- Integrated Wi-Fi (Intel 533AN)
- 2x 10/100/1000 Mbps network ports
- Audio amplifier with 2x2w speakers
- VESA 100 bracket for mounting metal stand included
- Customization available upon request



### Product Details

Product name: PPC-070C

Product Description: 7" Capacitive Touchscreen PC

## **PC System**

CPU: Intel® Celeron® DualCore N2807

Chipset: Intel® E3800

Graphic GPU: Intel® HD Graphics

Audio: Realtek 887 8 -channel high definition audio codec, Audio Amplifier EUA 2012A

Memory: 1x 2GB DDR3L SODIMM (expandable to 4GB)

Storage: Industrial 64GB SSD (SATA-DOM)

W-LAN: 2x Realtek PCIe GB LAN 8111G

Driver Support: Win7/8/10; Linux; 32Bit/64Bit

Preinstalled OS: Linux Ubuntu

## **LCD Panel**

IP rated front panel IP65

Screen diagonal (Inch/cm):7/17.78

Display active screen size:15.36×9.00

Aspect ratio:17:10

Physical resolution:1024×600

Maximum showable resolution (TPCs: external):1920×1200

Colours displayed:16.7M

Brightness (cd/m<sup>2</sup>):500

Contrast:700:1

Typical reaction time Tr/ Tf (ms):10/15

Visual Angle horizontal/vertical (°):150/145

Backlight / Backlight Lifetime (hours):LED / 20,000

## **Touch Panel**

Touch Technology Projected Capacitive 10-point Multitouch

Touch Connector USB

Touch Panel Drivers Windows; Linux; Mac; Android

Touch Life (Contacts)Unlimited

Surface Hardness 7H

## Operation / Mechanical

Operating Temperature (°C): -10 ~ +60

Humidity Range (RH): 20%-90%

Net weight (kg): 1.60

Gross weight (kg): 1.90 (incl. cartonage)

Housing material: Aluminum

Housing (cm) LxWxH: 19.60 x 13.80 x 4.85

Mounting: VESA 100

## Power

Power Indicator: Green LED

Power Supply: 100-240V ACDC active switching; 12V DC-Out

Working Power (V): 12

Power Consumption (W): 12

Stand-By Consumption (W): <1



## **Internal Connectors**

- 1x SO-DIMM Slot, max. 4GB, DDR3L-1333 Single channel memory
- 1x 12V DC power connector (2-pin)
- 1x 4-pin SATA power connector; 2x S-ATA 3GB/s ports
- 1x VGA pin header
- 1x SIM-card-Header (connected to MiniPCIe)
- 1x LVDS connector
- 1x S/PDIF output pin header
- 1x 5-pin LCD power connector
- 1x Line-Out / Mic-In audio pin header
- 1x 4-pin (2x2W) audio amplifier connector
- 1x PS/2 keyboard/mouse connector (6-pin)
- 1x USB 2.0 header supports additional 4x USB 2.0 ports
- 2x RS232 connectors
- 1x 8-bit Digital I/O interface
- 1x Chassis Fan connector

## **External Connectors**

- 1x Display port
- 1x USB 3.0, 3x USB 2.0 ports
- 2x COM port Full-PIN (RS232; 5V/12V)
- 2x 10/100/1000Mbit RJ45 Ports
- 1x MIC-In and Headphone-Out
- 1x 12V DC-In (screwable)
- 1x On/Off-button
- 2x W-LAN connector

## **Expansion Slots**

- 2x Mini Card slots with PCIe and USB interface (2 x Full Height/Half height changeable)

## **Included Accessories**

- Power Supply (see Power section)
- Driver DVD (Optional, FTP download provided by default)